

FR 7100 SCC | Full Extension Progressive Action Drawer Slide




Specifications

-  bottom mount
-  24.0 mm / 0.95 in.
-  dynamic up to 120 kg / 265 lbs. (full extension)
dynamic up to 105 kg / 231 lbs. (over extension)
dynamic up to 90 kg / 198 lbs. (heat-resistant)
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F

Characteristics

- high lateral stability
- cabinet profile with screw holes and drawer profile without holes
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F) – load capacity for full extension 90 kg (198 lbs.)

Dimensions



Length		Extension		Extension		Weight		Item No.	Item No.	Item No.
		full extension		over extension		per set		full extension	full extension heat-resistant	over extension
mm	inch	mm	inch	mm	inch	kg	lbs.			
400	15.75	385	15.16	460	18.11	3.51	7.74	7130	7140	*
450	17.72	435	17.13	510	20.08	4.00	8.82	7131	*	*
500	19.69	485	19.09	560	22.05	4.44	9.79	7132	7142	*
550	21.65	535	21.06	610	24.02	4.86	10.72	7133	7143	*
600	23.62	585	23.03	660	25.98	5.28	11.63	7134	7144	*
650	25.59	635	25.00	710	27.95	5.77	12.72	7135	7145	*
700	27.56	685	26.97	760	29.92	6.37	14.04	7136	*	82561
750	29.53	735	28.94	810	31.89	7.00	15.43	7137	*	*

Packing Unit – Sets per Box: from 400 to 600 mm: 4 | from 650 to 750 mm: 2

* on request