

FR 796 SCC OE

Over Extension Progressive Action Drawer Slide



Specifications

- bottom mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- 25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profile with screw holes

Dimensions



Length		Extension				Weight		Item No.	Item No.
mm	inch	mm	inch	kg	lbs.	per set	PU 1	PU 2	
300	11.81	335	13.19	1.46	3.22	► 70490	► 70490GV		
350	13.78	385	15.16	1.63	3.60	► 70491	► 70491GV		
400	15.75	460	18.11	1.83	4.03	► 70492	► 70492GV		
450	17.72	510	20.08	2.09	4.62	► 70493	► 70493GV		
500	19.69	560	22.05	2.34	5.16	► 70494	► 70494GV		
550	21.65	610	24.02	2.58	5.69	► 70495	► 70495GV		
600	23.62	660	25.98	2.84	6.25	► 70496	► 70496GV		
650	25.59	710	27.95	3.10	6.82	► 70497	► 70497GV		
700	27.56	760	29.92	3.35	7.37	► 70498	► 70498GV		
750	29.53	810	31.89	3.60	7.94	► 70499	► 70499GV		

Packing Unit

► in stock

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)