

FR 5400 | Full Extension Ball Bearing Slide




Specifications

-  side mount
-  19.5 mm / 0.77 in.
-  dynamic up to 250 kg / 550 lbs.
-  stainless steel ball bearing cages
-  steel, zinc plated

Characteristics

- symmetrical design – can therefore be used on both sides
- slides are non-detachable
- applicable for flat-mount installation – reduced load capacity

Dimensions



| Length | | Extension | | Weight | | Item No. |
|---------|------|-----------|------|---------|-------|-------------|
| | | | | per set | | zinc plated |
| mm | inch | mm | inch | kg | lbs. | |
| 203.2 | 8 | 203.2 | 8 | 1.95 | 4.30 | 5500 |
| 254.0 | 10 | 254.0 | 10 | 2.45 | 5.40 | 5501 |
| 304.8 | 12 | 304.8 | 12 | 2.98 | 6.56 | 5502 |
| 355.6 | 14 | 355.6 | 14 | 3.48 | 7.66 | 5503 |
| 406.4 | 16 | 406.4 | 16 | 4.00 | 8.82 | 5504 |
| 457.2 | 18 | 457.2 | 18 | 4.70 | 10.36 | 5505 |
| 508.0 | 20 | 508.0 | 20 | 5.20 | 11.46 | 5506 |
| 558.8 | 22 | 558.8 | 22 | 5.55 | 12.24 | 5507 |
| 609.6 | 24 | 609.6 | 24 | 6.05 | 13.34 | 5508 |
| 660.4 | 26 | 660.4 | 26 | 6.60 | 14.55 | 5509 |
| 711.2 | 28 | 711.2 | 28 | 7.10 | 15.65 | 5510 |
| 762.0 | 30 | 762.0 | 30 | 7.55 | 16.64 | 5511 |
| 812.8 | 32 | 812.8 | 32 | 8.10 | 17.86 | 5512 |
| 863.3 | 34 | 863.3 | 34 | 8.60 | 18.96 | 5513 |
| 914.4 | 36 | 914.4 | 36 | 9.10 | 20.06 | 5514 |
| 965.2 | 38 | 965.2 | 38 | 9.60 | 21.16 | 5515 |
| 1,016.0 | 40 | 1,016.0 | 40 | 10.30 | 22.71 | 5516 |
| 1,066.8 | 42 | 1,066.8 | 42 | 11.00 | 24.25 | 5517 |
| 1,117.6 | 44 | 1,117.6 | 44 | 11.40 | 25.13 | 5518 |
| 1,168.4 | 46 | 1,168.4 | 46 | 11.80 | 26.01 | 5519 |
| 1,219.2 | 48 | 1,219.2 | 48 | 12.30 | 27.12 | 5520 |
| 1,270.0 | 50 | 1,270.0 | 50 | 12.70 | 28.00 | 5521 |
| 1,320.0 | 52 | 1,320.0 | 52 | 13.20 | 29.10 | 5522 |
| 1,371.6 | 54 | 1,371.6 | 54 | 13.60 | 29.98 | 5523 |
| 1,422.4 | 56 | 1,422.4 | 56 | 14.10 | 31.09 | 5524 |
| 1,473.2 | 58 | 1,473.2 | 58 | 14.60 | 32.19 | 5525 |
| 1,524.0 | 60 | 1,524.0 | 60 | 15.40 | 33.95 | 5526 |

Packing Unit – Sets per Box: from 203.2 to 609.6 mm: 4 | from 660.4 to 863.3 mm: 2 | from 914.4 to 1,524.0 mm: 1