

FR 7100 SCC US

Full Extension Progressive Action Drawer Slide




Specifications

-  bottom mount
-  24.0 mm / 0.95 in.
-  dynamic up to 120 kg / 265 lbs. (full extension)
-  dynamic up to 105 kg / 231 lbs. (over extension)
-  dynamic up to 90 kg / 198 lbs. (heat-resistant)
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F

Characteristics

- high lateral stability
- cabinet profile with screw holes and drawer profile without holes
- narrow drawer profile for standard serving pans
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F) – load capacity for full extension 90 kg (198 lbs.)

Dimensions



| Length | | Extension | | Extension | | Weight | | Item No. | Item No. |
|--------|-------|----------------|-------|----------------|-------|---------|-------|----------------|----------------|
| | | full extension | | over extension | | per set | | full extension | over extension |
| mm | inch | mm | inch | mm | inch | kg | lbs. | | |
| 400 | 15.75 | 385 | 15.16 | 460 | 18.11 | 3.52 | 7.77 | 83146 | * |
| 450 | 17.72 | 435 | 17.13 | 510 | 20.08 | * | * | * | * |
| 500 | 19.69 | 485 | 19.09 | 560 | 22.05 | * | * | * | * |
| 550 | 21.65 | 535 | 21.06 | 610 | 24.02 | 4.70 | 10.35 | 82186T | * |
| 600 | 23.62 | 585 | 23.03 | 660 | 25.98 | 5.13 | 11.30 | 82187T | * |
| 650 | 25.59 | 635 | 25.00 | 710 | 27.95 | 5.53 | 12.18 | 82188T | * |
| 700 | 27.56 | 685 | 26.97 | 760 | 29.92 | * | * | * | * |
| 750 | 29.53 | 735 | 28.94 | 810 | 31.89 | * | * | * | * |

Packing Unit – Sets per Box: from 400 to 600 mm: **4** | from 650 to 750 mm: **2**

* on request