# FR 790 SCC | Full Extension Progressive Action Drawer Slide

## Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 68 kg / 150 lbs. (full extension)
  dynamic up to 53 kg / 120 lbs. (over extension)
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

## Characteristics

- high lateral stability
- cabinet and drawer profile with screw holes
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F) – load capacity 40 kg (90 lbs.) for over extension (drawer profile without screw holes)

## Dimensions




| Length | | Extension | | Extension | | Weight | | Item No. | Item No. | Item No. |
|---|---|---|---|---|---|---|---|---|---|---|
| | | full extension | | over extension | | per set | | full extension | over extension | over extension heat-resistant |
| **mm** | **inch** | mm | inch | mm | inch | kg | lbs. | | | |
| **350** | **13.78** | 335 | 13.19 | 410 | 16.14 | 1.62 | 3.57 | **7900** | * | **7970** |
| **400** | **15.75** | 385 | 15.16 | 460 | 18.11 | 1.81 | 3.99 | **7901** | * | * |
| **450** | **17.72** | 435 | 17.13 | 510 | 20.08 | 2.04 | 4.49 | **7902** | * | **7972** |
| **500** | **19.69** | 485 | 19.09 | 560 | 22.05 | 2.28 | 5.02 | **7903** | * | **7973** |
| **550** | **21.65** | 535 | 21.06 | 610 | 24.02 | 2.49 | 5.50 | **7904** | **7924** | **7974** |
| **600** | **23.62** | 585 | 23.03 | 660 | 25.98 | 2.73 | 6.01 | **7905** | * | **7975** |
| **650** | **25.59** | 635 | 25.00 | 710 | 27.95 | 2.98 | 6.57 | **7906** | **7926** | * |
| **700** | **27.56** | 685 | 26.97 | 760 | 29.92 | 3.18 | 7.00 | **7907** | * | * |
| **750** | **29.53** | 735 | 28.94 | 810 | 31.89 | * | * | * | * | * |

**Packing Unit – Sets per Box, all Lengths: 5**

* on request

Fulterer®